SamHop Microelectronics Corp.

STM4470A


May, 10 2007


N-Channel Enhancement Mode Field Effect Transistor

PRODUCT SUMMARY		
V_{DSS}	I_D	$R_{DS(ON)}$ (m Ω) Max
40V	10A	10.5 @ V_{GS} = 10V
		13.5 @ V_{GS} = 4.5V

FEATURES

- Super high dense cell design for low $R_{DS(ON)}$.
- Rugged and reliable.
- Surface Mount Package.
- ESD Protected.





ABSOLUTE MAXIMUM RATINGS (T_A=25 C unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	40	V
Gate-Source Voltage	V_{GS}	±20	V
Drain Current-Continuous [a] @T_J=25°C	I_D	10	A
-Pulsed [b]	I_{DM}	39	A
Drain-Source Diode Forward Current [a]	I_S	1.7	A
Maximum Power Dissipation [a]	P_D	2.5	W
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	°C

THERMAL CHARACTERISTICS

Thermal Resistance, Junction-to-Ambient [a]	$R_{\theta JA}$	50	°C/W

STM4470A

ELECTRICAL CHARACTERISTICS (T_A=25°C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ [C]	Max	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V, I_D=250uA	40			V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=32V, V_{GS}=0V			1	uA
Gate-Body Leakage	I_{GSS}	V_{GS}=±20V, V_{DS}=0V			±10	uA
ON CHARACTERISTICS [b]						
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=250uA	1	1.8	3	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	V_{GS}=10V, I_D=10A		9	10.5	m ohm
		V_{GS}=4.5V, I_D=6A		11.5	13.5	m ohm
On-State Drain Current	$I_{D(ON)}$	V_{DS}=10V, V_{GS}=10V	20			A
Forward Transconductance	g_{FS}	V_{DS}=10V, I_D=10A		23		S
DYNAMIC CHARACTERISTICS [c]						
Input Capacitance	C_{ISS}	V_{DS}=20V, V_{GS}=0V f=1.0MHz		1200		pF
Output Capacitance	C_{OSS}			230		pF
Reverse Transfer Capacitance	C_{RSS}			150		pF
SWITCHING CHARACTERISTICS [c]						
Turn-On Delay Time	$t_{D(ON)}$	V_{DD}=15V I_D=1A V_{GS}=10V R_{GEN}=6 ohm		19		ns
Rise Time	t			20		ns
Turn-Off Delay Time	$t_{D(OFF)}$			62		ns
Fall Time	t			15		ns
Total Gate Charge	Q_g	V_{DS}=15V, I_D=10A, V_{GS}=10V		22		nC
		V_{DS}=15V, I_D=10A, V_{GS}=4.5V		10		nC
Gate-Source Charge	Q_{gs}	V_{DS}=15V, I_D=10A V_{GS}=10V		2.6		nC
Gate-Drain Charge	Q_{gd}			5.5		nC

STM4470A

ELECTRICAL CHARACTERISTICS (T_A=25°C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ [c]	Max	Unit
DRAIN-SOURCE DIODE CHARACTERISTICS [b]						
Diode Forward Voltage	V_{SD}	V_{GS} = 0V, Is =1.7A		0.73	1.2	V

Notes

a.Surface Mounted on FR4 Board, t≤10sec.
b.Pulse Test:Pulse Width≤300us, Duty Cycle≤2%.
c.Guaranteed by design, not subject to production testing.




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. On-Resistance Variation with Drain Current and Temperature




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature




Figure 7. On-Resistance vs. Gate-Source Voltage




Figure 8. Body Diode Forward Voltage Variation with Source Current

STM4470A




Figure 9. Capacitance




Figure 10. Gate Charge




Figure 11.switching characteristics





Figure 12. Maximum Safe Operating Area




Normalized Thermal Transient Impedance Curve

STM4470A

PACKA GE OUTLINE DIMENSIONS


SO-8



SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	1.35	1.75	0.053	0.069
A1	0.10	0.25	0.004	0.010
D	4.80	4.98	0.189	0.196
E	3.81	3.99	0.150	0.157
H	5.79	6.20	0.228	0.244
L	0.41	1.27	0.016	0.050
θ	0°	8°	0°	8°

SO-8 Tape and Reel Data


SO-8 Carrier Tape



unit:mm

PACKAGE	A0	B0	K0	D0	D1	E	E1	E2	P0	P1	P2	T
SOP 8N 150mil	6.40	5.20	2.10	ϕ1.5 (MIN)	ϕ1.5 + 0.1 - 0.0	12.0 ±0.3	1.75	5.5±0.05	8.0	4.0	2.0±0.05	0.3±0.05

SO-8 Reel



UNIT:mm

TAPE SIZE	REEL SIZE	M	N	W	W1	H	K	S	G	R	V
12 mm	ϕ330	330 ± 1	62 ±1.5	12.4+ 0.2	16.8- 0.4	ϕ12.75 + 0.15	---	2.0±0.15	---	---	---