



SamHop Microelectronics Corp.




STU312D

Oct 08 2008

Dual Enhancement Mode Field Effect Transistor (N and P Channel)

PRODUCT SUMMARY (N-Channel)		
V _{DSS}	I _D	R _{D(S(ON))} (mΩ) Max
30V	18A	24 @ V _{GS} = 10V
		36 @ V _{GS} = 4.5V

PRODUCT SUMMARY (P-Channel)		
V _{DSS}	I _D	R _{D(S(ON))} (mΩ) Max
-30V	-14A	34 @ V _{GS} = -10V
		54 @ V _{GS} = -4.5V



ABSOLUTE MAXIMUM RATINGS (T_A=25°C unless otherwise noted)

Parameter	Symbol	N-Channel	P-Channel	Unit
Drain-Source Voltage	V _{DS}	30	-30	V
Gate-Source Voltage	V _{GS}	±24	±24	V
Drain Current-Continuous @ T _c	25°C	I _D	18	A
	70°C		15	A
-Pulsed ^a	I _{DM}	50	-50	A
Drain-Source Diode Forward Current	I _S	10	-6	A
Maximum Power Dissipation	T _c = 25°C	P _D	11	W
	T _c = 70°C		7.7	
Operating Junction and Storage Temperature Range	T _J , T _{STG}	-55 to 175		°C

THERMAL CHARACTERISTICS

Thermal Resistance, Junction-to-Case	R _{θJC}	13.6	°C/W
Thermal Resistance, Junction-to-Ambient	R _{θJA}	120	°C/W

STU312D

N-Channel ELECTRICAL CHARACTERISTICS (TA = 25°C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250μA	30			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =24V, V _{GS} =0V		1		μA
Gate-Body Leakage	I _{GSS}	V _{GS} =±24V, V _{DS} =0V		±10		μA
ON CHARACTERISTICS ^a						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250μA	1	1.8	3	V
Drain-Source On-State Resistance	R _{D(S)ON}	V _{GS} =10V, I _D =10A		18	24	m ohm
		V _{GS} =4.5V, I _D =8A		24	36	m ohm
On-State Drain Current	I _{D(ON)}	V _{DS} =5V, V _{GS} =4.5V	20			A
Forward Transconductance	g _{FS}	V _{DS} =10V, I _D = 10A		15		S
DYNAMIC CHARACTERISTICS ^b						
Input Capacitance	C _{ISS}	V _{DS} =15V, V _{GS} =0V f=1.0MHz		640		pF
Output Capacitance	C _{OSS}			180		pF
Reverse Transfer Capacitance	C _{RSS}			110		pF
Gate resistance	R _g	V _{GS} =0V, V _{DS} =0V, f=1.0MHz		0.5		ohm
SWITCHING CHARACTERISTICS ^b						
Turn-On Delay Time	t _{D(ON)}	V _{DD} = 15V I _D = 1 A V _{GS} = 10V R _{GEN} = 6 ohm		13		ns
Rise Time	t _r			12		ns
Turn-Off Delay Time	t _{D(OFF)}			40		ns
Fall Time	t _f			7		ns
Total Gate Charge	Q _g	V _{DS} =15V, I _D =20A, V _{GS} =10V		13		nC
		V _{DS} =15V, I _D =20A, V _{GS} =4.5V		6.8		nC
Gate-Source Charge	Q _{gs}	V _{DS} =15V, I _D = 20 A V _{GS} =10V		1.5		nC
Gate-Drain Charge	Q _{gd}			3.5		nC

STU312D

P-Channel ELECTRICAL CHARACTERISTICS (TA = 25 °C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BVDSS	V _{GS} =0V, I _D =-250uA	-30			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =-24V, V _{GS} =0V			-1	uA
Gate-Body Leakage	I _{GSS}	V _{GS} =±24V, V _{DS} =0V			±10	uA
ON CHARACTERISTICS ^a						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =-250uA	-1	-1.7	-3	V
Drain-Source On-State Resistance	R _{D(S(ON))}	V _{GS} =-10V, I _D = -6A		27	34	m ohm
		V _{GS} =-4.5V, I _D = -4A		39	54	m ohm
On-State Drain Current	I _{D(ON)}	V _{DS} = -5V, V _{GS} = -10V	-20			A
Forward Transconductance	g _{FS}	V _{DS} = -10V, I _D =-6A		10		S
DYNAMIC CHARACTERISTICS ^b						
Input Capacitance	C _{ISS}	V _{DS} = -15V, V _{GS} = 0V f = 1.0MHz		800		pF
Output Capacitance	C _{OSS}			215		pF
Reverse Transfer Capacitance	C _{RSS}			120		pF
Gate resistance	R _g	V _{GS} =0V, V _{DS} = 0V, f=1.0MHz		4		ohm
SWITCHING CHARACTERISTICS ^b						
Turn-On Delay Time	t _{D(ON)}	V _{DD} = -15V I _D = -1A V _{GS} = -10V R _{GEN} = 6 ohm		12		ns
Rise Time	t _r			18		ns
Turn-Off Delay Time	t _{D(OFF)}			68		ns
Fall Time	t _f			38		ns
Total Gate Charge	Q _g	V _{DS} =-15V, I _D =-20A, V _{GS} =-10V		15		nC
		V _{DS} =-15V, I _D =-20A, V _{GS} =-4.5V		7		nC
Gate-Source Charge	Q _{gs}	V _{DS} =-15V, I _D = -20 A V _{GS} =-10V		1.3		nC
Gate-Drain Charge	Q _{gd}			5		nC

STU312D

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ ^c	Max	Unit
DRAIN-SOURCE DIODE CHARACTERISTICS ^b						
Diode Forward Voltage	V_{SD}	$V_{GS} = 0\text{V}, I_S = 10\text{A}$ $V_{GS} = 0\text{V}, I_S = -6\text{A}$	N-Ch P-Ch	0.9 -0.9	1.3 -1.3	V

Notes

a. Pulse Test: Pulse Width $\leq 300 \mu\text{s}$, Duty Cycle $\leq 2\%$.

b. Guaranteed by design, not subject to production testing.

N-Channel




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. On-Resistance Variation with Drain Current and Temperature

STU312D




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature




Figure 7. On-Resistance vs. Gate-Source Voltage




Figure 8. Body Diode Forward Voltage Variation with Source Current

STU312D




Figure 10. Capacitance




Figure 11. Gate Charge




Figure 12. switching characteristics




Figure 13. Maximum Safe Operating Area




Figure 14. Normalized Thermal Transient Impedance Curve

STU312D

P-Channel




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. On-Resistance Variation with Drain Current and Temperature

STU312D




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature




Figure 7. On-Resistance vs. Gate-Source Voltage




Figure 8. Body Diode Forward Voltage Variation with Source Current

STU312D




Figure 10. Capacitance




Figure 11. Gate Charge




Figure 12. switching characteristics




Figure 13. Maximum Safe Operating Area





Figure 14. Normalized Thermal Transient Impedance Curve

STU312D

PACKAGE OUTLINE DIMENSIONS

TO-252-4L




REF .	Millimeters	
	MIN	MAX
A	6.40	6.80
B	5.2	5.50
C	6.80	10.20
D	2.20	3.00
P	1.27 REF.	
S	0.50	0.80
G	0.40	0.60
H	2.20	2.40
J	0.45	0.60
K	0	0.15
L	0.90	1.50
M	5.40	5.80

STU312D




TO-252-4L Tape and Reel Data

TO-252-4L Carrier Tape



symbol	A_0	B_0	K_0	P_0	P_1	P_2	T
Spec	6.96 ± 0.1	10.49 ± 0.1	2.79 ± 0.1	4.0 ± 0.1	8.0 ± 0.10	2.0 ± 0.05	0.33 ± 0.013
symbol	E	F	D_0	D_1	W	$10P_0$	
Spec	1.75 ± 0.1	7.5 ± 0.05	1.55 ± 0.05	1.5 ± 0.25	16.0 ± 0.3	40.0 ± 0.2	

TO-252-4L Reel



UNIT:mm

Width of carrier tape	8	12	16	24	32	44	56
$A \pm 0.1$	9.4	13.4	17.4	25.4	33.4	45.4	57.4
B	2.3	2.3	2.3	2.3	2.3	2.3	2.3
ϕC	100	100	100	100	100	100	100