



SamHop Microelectronics Corp.

**STU/D339S**


Ver 1.0

N-Channel Logic Level Enhancement Mode Field Effect Transistor

PRODUCT SUMMARY		
VDSS	ID	RDS(ON) (mΩ) Max
30V	40A	9.6 @ VGS=10V
		15 @ VGS=4.5V

FEATURES

- Super high dense cell design for low RDS(ON).
- Rugged and reliable.
- TO-252 and TO-251 Package.



ABSOLUTE MAXIMUM RATINGS ($T_C=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Limit	Units
V_{DS}	Drain-Source Voltage	30	V
V_{GS}	Gate-Source Voltage	± 20	V
I_D	Drain Current-Continuous	25°C	A
		70°C	A
I_{DM}	-Pulsed ^a	117	A
E_{AS}	Single Pulse Avalanche Energy ^c	56	mJ
P_D	Maximum Power Dissipation	25°C	W
		70°C	W
T_J, T_{STG}	Operating Junction and Storage Temperature Range	-55 to 150	$^\circ\text{C}$

THERMAL CHARACTERISTICS

$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	3	$^\circ\text{C/W}$
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	50	$^\circ\text{C/W}$

STU/D339S

Ver 1.0

ELECTRICAL CHARACTERISTICS (T_c=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
OFF CHARACTERISTICS						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V , I _D =250uA	30			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =24V , V _{GS} =0V			1	uA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±20V , V _{DS} =0V			±100	nA
ON CHARACTERISTICS						
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250uA	1.0	1.7	3	V
R _{DSON}	Drain-Source On-State Resistance	V _{GS} =10V , I _D =20A		8.2	9.6	m ohm
		V _{GS} =4.5V , I _D =16A		11.5	15	m ohm
g _{FS}	Forward Transconductance	V _{DS} =10V , I _D =20A		55		S
DYNAMIC CHARACTERISTICS ^b						
C _{iss}	Input Capacitance	V _{DS} =15V,V _{GS} =0V f=1.0MHz		900		pF
C _{oss}	Output Capacitance			161		pF
C _{rss}	Reverse Transfer Capacitance			124		pF
SWITCHING CHARACTERISTICS ^b						
t _{D(ON)}	Turn-On Delay Time	V _{DD} =15V I _D =1A V _{GS} =10V R _{GEN} = 6 ohm		17		ns
t _r	Rise Time			18		ns
t _{D(OFF)}	Turn-Off Delay Time			18		ns
t _f	Fall Time			46		ns
Q _g	Total Gate Charge	V _{DS} =15V,I _D =20A,V _{GS} =10V		14		nC
		V _{DS} =15V,I _D =20A,V _{GS} =4.5V		6.5		nC
Q _{gs}	Gate-Source Charge	V _{DS} =15V,I _D =20A, V _{GS} =10V		1.8		nC
Q _{gd}	Gate-Drain Charge			4.1		nC
DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS						
V _{SD}	Diode Forward Voltage	V _{GS} =0V,I _S =2A		0.77	1.3	V
Notes						
a.Pulse Test:Pulse Width ≤ 300us, Duty Cycle ≤ 2%.						
b.Guaranteed by design, not subject to production testing.						
c.Starting T _J =25°C,L=0.5mH,V _{DD} = 20V.(See Figure13)						

Aug,17,2012




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. On-Resistance Variation with Drain Current and Temperature




Figure 5. Gate Threshold Variation with Temperature






Figure 6. Breakdown Voltage Variation with Temperature




V_{GS}, Gate-to-Source Voltage(V)

Figure 7. On-Resistance vs. Gate-Source Voltage




V_{SD}, Body Diode Forward Voltage(V)

Figure 8. Body Diode Forward Voltage Variation with Source Current



V_{DS}, Drain-to-Source Voltage(V)

Figure 9. Capacitance



Q_g , Total Gate Charge(nC)

Figure 10. Gate Charge




Figure 11. switching characteristics






Figure 12. Maximum Safe Operating Area



Uncamped Inductive Test Circuit

Figure 13a.



Unclamped Inductive Waveforms

Figure 13b.





Figure 14. Normalized Thermal Transient Impedance Curve

PACKAGE OUTLINE DIMENSIONS


TO-251



SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.20	2.40	0.087	0.095
A1	1.100	1.300	0.043	0.051
B1	0.650	1.050	0.026	0.041
b	0.500	0.900	0.020	0.035
b1	0.400	0.800	0.016	0.32
C	0.400	0.600	0.016	0.024
D	6.700	7.300	0.264	0.287
D1	5.400	5.650	0.213	0.222
E	6.40	6.650	0.252	0.262
e	2.100	2.500	0.083	0.098
F	0.400	0.600	0.016	0.024
L	7.000	8.000	0.276	0.315
L1	1.300	1.700	0.051	0.067
L2	0.700	0.900	0.028	0.035
L3	1.400	1.800	0.055	0.071


STU/D339S

Ver 1.0




TO-251 Tube/TO-252 Tape and Reel Data

TO-251 Tube






TO-252 Carrier Tape



UNIT:mm

PACKAGE	A0	B0	K0	D0	D1	E	E1	E2	P0	P1	P2	T
TO-252 (16 mm)	6.96 ±0.1	10.49 ±0.1	2.79 ±0.1	ϕ 2	ϕ 1.5 + 0.1 - 0	16.0 ±0.3	1.75 ±0.1	7.5 ±0.15	8.0 ±0.1	4.0 ±0.1	2.0 ±0.15	0.3 ±0.05

TO-252 Reel



UNIT:mm

TAPE SIZE	REEL SIZE	M	N	W	T	H	K	S	G	R	V
16 mm	ϕ 330	ϕ 330 ± 0.5	ϕ 97 ± 1.0	17.0 + 1.5 - 0	2.2	ϕ 13.0 + 0.5 - 0.2	10.6	2.0 ± 0.5	---	---	---