SamHop Microelectronics Corp.

STU/D2455PLS


Dec 30, 2005

P-Channel Enhancement Mode Field Effect Transistor


PRODUCT SUMMARY		
V_{DSS}	I_D	$R_{DS(ON)}$ (mΩ) Max
-55V	-24	42 @ V_{GS} = -10V
		55 @ V_{GS} = -4.5V

FEATURES


- Super high dense cell design for low $R_{DS(ON)}$.
- Rugged and reliable.
- TO-252 and TO-251 Package.



STU SERIES
TO-252AA(D-PAK)



STD SERIES
TO-251(I-PAK)



ABSOLUTE MAXIMUM RATINGS (T_A=25°C unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage Rating	V_{spike}[c]	-60	V
Drain-Source Voltage	V_{DS}	-55	V
Gate-Source Voltage	V_{GS}	±20	V
Drain Current-Continuous @Tc=25°C	I_D	-24	A
-Pulsed[a]	I_{DM}	-72	A
Drain-Source Diode Forward Current	I_S	-20	A
Maximum Power Dissipation @Tc=25°C	P_D	50	W
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 175	°C

THERMAL CHARACTERISTICS

Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	3	°C/W
Thermal Resistance, Junction-to-Ambient	$R_{\theta JA}$	50	°C/W

STU/D2455PLS

ELECTRICAL CHARACTERISTICS (T_C=25°C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ [c]	Max	Unit
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V, I_D=-250uA	-55			V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=-44V, V_{GS}=0V			-1	uA
Gate-Body Leakage	I_{GSS}	V_{GS}=±20V, V_{DS}=0V			±100	nA
ON CHARACTERISTICS [a]						
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=-250uA	-1	-1.7	-3	V
Drain-Source On-State Resistance	$R_{DS(ON)}$	V_{GS}=-10V, I_D=-10A		33	42	m ohm
		V_{GS}=-4.5V, I_D=-6A		42	55	m ohm
On-State Drain Current	$I_{D(ON)}$	V_{DS}=-10V, V_{GS}=-10V	-24			A
Forward Transconductance	g_{FS}	V_{DS}=-10V, I_D=-10A		16		S
DYNAMIC CHARACTERISTICS [b]						
Input Capacitance	C_{ISS}	V_{DS}=-30V, V_{GS}=0V f=1.0MHz		1730		pF
Output Capacitance	C_{OSS}			185		pF
Reverse Transfer Capacitance	C_{RSS}			125		pF
Gate resistance	Rg	V_{GS}=0V, V_{DS}=0V, f=1.0MHz		1.7		ohm
SWITCHING CHARACTERISTICS [b]						
Turn-On Delay Time	$t_{D(ON)}$	V_{DD}=-30V I_D=-1 A V_{GS}=-10V R_{GEN}=6 ohm		21		ns
Rise Time	t_r			25		ns
Turn-Off Delay Time	$t_{D(OFF)}$			127		ns
Fall Time	t_f			35		ns
Total Gate Charge (10V)	Q_g	V_{DS}=-30V, I_D=-10A V_{GS}=-10V		31		nC
Total Gate Charge (4.5V)				13.5		nC
Gate-Source Charge	Q_{gs}			3.5		nC
Gate-Drain Charge	Q_{gd}			7		nC

STU/D2455PLS

ELECTRICAL CHARACTERISTICS (T_C=25°C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
DRAIN-SOURCE DIODE CHARACTERISTICS [a]						
Diode Forward Voltage	V_{SD}	V_{GS} = 0V, Is = -10A		-0.92	-1.3	V

Notes

a.Pulse Test:Pulse Width ≤ 300us, Duty Cycle ≤ 2%.

b.Guaranteed by design, not subject to production testing.

c.Guaranteed when external Rg=6 ohm and tf < tf max




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. On-Resistance Variation with Drain Current and Temperature

STU/D2455PLS




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Breakdown Voltage Variation with Temperature




Figure 7. On-Resistance vs. Gate-Source Voltage




Figure 8. Body Diode Forward Voltage Variation with Source Current

STU/D2455PLS




Figure 9. Capacitance




Figure 10. Gate Charge




Figure 11.switching characteristics




Figure 10. Maximum Safe Operating Area

STU/D2455PLS




Figure 11. Switching Test Circuit




Figure 12. Switching Waveforms





Figure 13. Normalized Thermal Transient Impedance Curve

STU/D2455PLS

PACKAGE OUTLINE DIMENSIONS

TO-251




SYMBOL	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.100	2.500	0.083	0.098
A1	0.350	0.650	0.014	0.026
B	0.400	0.800	0.016	0.031
B1	0.650	1.050	0.026	0.041
B2	0.500	0.900	0.020	0.035
C	0.400	0.600	0.016	0.024
D	5.300	5.700	0.209	0.224
D1	4.900	5.300	0.193	0.209
D2	6.700	7.300	0.264	0.287
D3	7.000	8.000	0.276	0.315
H	13.700	15.300	0.539	0.602
E	6.300	6.700	0.248	0.264
E1	4.600	4.900	0.181	0.193
E2	4.800	5.200	0.189	0.205
L	1.300	1.700	0.051	0.067
L1	1.400	1.800	0.055	0.071
L2	0.500	0.900	0.020	0.035
P	2.300 BSC		0.091 BSC	

STU/D2455PLS

PACKAGE OUTLINE DIMENSIONS

TO-252




SYMBOLS	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.100	2.500	0.083	0.098
A1	0.000	0.200	0.000	0.008
b	0.400	0.889	0.016	0.035
b1	0.770	1.140	0.030	0.045
b2	4.800	5.460	0.189	0.215
C	0.400	0.600	0.016	0.024
D	5.300	6.223	0.209	0.245
D1	4.900	5.515	0.193	0.217
E	6.300	6.731	0.248	0.265
E1	4.400	5.004	0.173	0.197
e	2.290 REF		0.090 BSC	
H	8.900	10.400	0.350	0.409
L	1.397	1.770	0.055	0.070
L1	2.743 REF.		0.108 REF.	
L2	0.508 REF.		0.020 REF.	
L3	0.890	1.700	0.035	0.067
L4	0.500	1.100	0.020	0.043
θ	0°	10°	0°	10°
θ1	7° REF.		7° REF.	


STU/D2455PLS

TO251 Tube/TO-252 Tape and Reel Data

TO-251 Tube




TO-252 Carrier Tape



UNIT:㎜

PACKAGE	A0	B0	K0	D0	D1	E	E1	E2	P0	P1	P2	T
TO-252 (16 ㎜)	6.80 ±0.1	10.3 ±0.1	2.50 ±0.1	ϕ2	ϕ1.5 + 0.1 - 0	16.0 0.3±	1.75 0.1±	7.5 ±0.15	8.0 ±0.1	4.0 ±0.1	2.0 ±0.15	0.3 ±0.05

TO-252 Reel



UNIT:㎜

TAPE SIZE	REEL SIZE	M	N	W	T	H	K	S	G	R	V
16 ㎜	ϕ 330	ϕ330 ± 0.5	ϕ97 ± 1.0	17.0 + 1.5 - 0	2.2	ϕ13.0 + 0.5 - 0.2	10.6	2.0 ±0.5	---	---	---